

EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	478	multiple with semaphore	US-PGPUB; USPAT; EPO	OR	ON	2007/04/01 19:06
L2	6	(multiple and semaphore).ti.	US-PGPUB; USPAT; EPO	OR	ON	2007/04/01 19:00
L3	6	(multiple and semaphore).ti. and (semaphore lock status)	US-PGPUB; USPAT; EPO	OR	ON	2007/04/01 19:00
L4	32	(multiple with semaphore) same (copy replicat\$3)	US-PGPUB; USPAT; EPO	OR	ON	2007/04/01 19:08
L5	18	(multiple with semaphore) same (copy replicat\$3)and @ad<"20021127"	US-PGPUB; USPAT; EPO	OR	ON	2007/04/01 19:08
L6	18	(multiple with semaphore) same (copy replicat\$3) and (lock semaphore) and @ad<"20021127"	US-PGPUB; USPAT; EPO	OR	ON	2007/04/01 19:08

[Google](#)[Web](#) [Images](#) [Video](#) [News](#) [Maps](#) [more »](#)[Advanced Search](#)
[Preferences](#)**Web**Results 1 - 10 of about 741,000 for **replicate identifier status lock**. (0.25 seconds)Did you mean: **duplicate** identifier status lock**[PDF] CITI - ARC Joint Project Status Report**File Format: PDF/Adobe Acrobat - [View as HTML](#)NFSv4 has a means of providing file system **replication** and migration services ... of a call that takes a client **identifier** and a **status** (as an integer). ...www.citi.umich.edu/projects/cluster_nfsv4/CITI-IBM-A0550295-report.pdf - Similar pages**WebDAV Status Codes: 100s and 200s**

LOCK Method, The LOCK method was used to perform a multi-resource lock request.

[WebDAV] ... See HTTP and WebDAV Methods for **Replication**. ...msdn2.microsoft.com/en-us/library/aa142865.aspx - 13k - Cached - Similar pages**WebDAV Status Codes: 300s and 400s**PUT Method, COPY Method, In a WebDAV **replication** context, either the If:(<resourcetag>) or If: ... The **lock** token is needed to refresh the **lock**. [WebDAV] ...msdn2.microsoft.com/en-us/library/aa142868.aspx - 19k - Cached - Similar pages[More results from msdn2.microsoft.com]**CiscoSecure ACS for UNIX, 2.3(5) - CiscoSecure ACS Database ...**Setting Up Database **Replication** among CiscoSecure ACSes ... Name of the CiscoSecure ACS database server on which this **lock** was issued. host_name ...www.cisco.com/en/US/products/sw/secursw/ps4911/products_user_guide_chapter09186a00803deb1d.html - 73k -

Cached - Similar pages

CiscoSecure ACS Database StructureSee "Setting Up Database **Replication** among CiscoSecure ACSes," for details. ... Name of the CiscoSecure ACS database server on which this **lock** was issued. ...www.cisco.com/univercd/cc/td/doc/product/access/acs_soft/cs_unx/acsu235/app_f.htm -

63k - Cached - Similar pages

[More results from www.cisco.com]**ONLamp.com -- Live Backups of MySQL Using Replication**Also, run SHOW SLAVE STATUS; on the slave to see if everything looks okay. It will list the last error number and message if **replication** failed after ...www.onlamp.com/pub/a/onlamp/2005/06/16/MySQLian.html - 63k - Cached - Similar pages**Informix® Dynamic Server V10.00.xC4 Setting Up Enterprise Replication**If you have not completed the module, "Enterprise **Replication**, ... "R" in the participant server **identifier**, and ignore CR Start the **replicate** Confirm that ...[publib.boulder.ibm.com/.../IDSv10_ER_Configuration/player.html?](http://publib.boulder.ibm.com/.../IDSv10_ER_Configuration/player.html?dmuid=20061231215552578547)[dmuid=20061231215552578547](http://publib.boulder.ibm.com/.../IDSv10_ER_Configuration/player.html?dmuid=20061231215552578547) - 28k - Cached - Similar pages**Glossary**A physical **lock** is an example of a negotiable **lock**. nested table expression: A fullselect in a FROM clause (surrounded by parentheses). network **identifier** ...publib.boulder.ibm.com/infocenter/dzichelp/v2r2/topic/com.ibm.dzic.doc.gloss/icglosn.htm -

14k - Cached - Similar pages

[More results from publib.boulder.ibm.com]**IBM Globalization - Terminology - terms T and U**See also row **identifier**, row **lock**. table-mode processing: In SQL **replication**, a type of **replication** subscription-set processing in which the Apply program ...

[Paper] Design and Implementation of SSDLM: A Distributed Lock ...

The attributes of RLT consists of a resource name to be locked, a **lock** mode, a requestor **identifier**, and **status** to indicate whether a read lock request is ...

www.actapress.com/PDFViewer.aspx?paperId=17774 - Similar pages

Did you mean to search for: **duplicate** identifier status lock

Result Page: 1 2 3 4 5 6 7 8 9 10 **Next**

Try Google Desktop: search your computer as easily as you search the web.

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2007 Google